




Input Parameters	
Input Voltage Range	220-240 Vac
Input Current	<0.03A
Power Factor	> 0.32
Frequency	50Hz
Ambient Temperature	0-40C
Class	II
Maximum Input Power (While Charging Battery)	2.5W
Average Input Power (Not Charging Battery)	2.0W

Emergency Parameters	
Emergency Duration	180minutes
Battery Code(s)	zc-batt-1A1-ACA
Battery Type	LiFePO4
Input Battery Voltage	2.0-4.0 Vdc
Output Battery Voltage	2.0-4.0 Vdc
Input Battery Current	330mA
Output Battery Current	0.08a
Charging Time	24 hours
Emergency Output Power	0.65 W
Exit Sign View Distance	30m

Mechanical	
Material	Polycarbonate
Product Colour	RAL9011
Wiring Type	Hard wired (16mm2)
Mounting	Surface Mount/Wall Mount
Ingress Protection	IP20
Product Dimension Length	326mm
Product Dimension Height	211mm
Product Dimension Width	80mm

Standards	
IEC 60598-1	Yes
IEC 60598-2-22	Yes
IEC 62034	Yes

Product Line Drawing



Packaging	
Carton Length	0..
Carton Width	0..
Carton Height	0..
Unit Net Weight	0.00kg
Carton Gross Weight	0.00..
EAN 13	6971103537776
EAN 14	
Carton Quantity	Carton 8

Photometrics