




02	
Input Parameters	
Input Voltage Range	220-240 Vac
Input Current	<0.03A
Power Factor	> 0.32
Frequency	50Hz
Ambient Temperature	0-40C
Class	II
Maximum Input Power (While Charging Battery)	2.5 W
Average Input Power (Not Charging Battery)	2.3W

DALI Parameters	
Input Current	2 mA
Over Voltage Protection	Yes
Input Voltage	9.5 - 22.5 Vdc


Emergency Parameters	
Emergency Duration	180minutes
Battery Code(s)	zc-batt-1A1-ACA
Battery Type	LiFePO4
Input Battery Voltage	2.0-4.0 Vdc
Output Battery Voltage	2.0-3.65 Vdc
Input Battery Current	300mA
Output Battery Current	0.08A
Charging Time	24 hours
Emergency Output Power	0.6 W
Exit Sign View Distance	30m


Mechanical	
Material	Polycarbonate
Product Colour	RAL9003
Wiring Type	Push Terminal (0.5-2.5mm2)
Mounting	Surface mount/Jack chain mount/Wall mount
Ingress Protection	IP20
Product Dimension Length	315mm
Product Dimension Height	204mm
Product Dimension Width	52mm


Product Line Drawing



Product Install Picture

















Standards	
IEC 60598-1	Yes
IEC 60598-2-22	Yes
IEC 62034	Yes

Required Safety Warnings

- · This product must only be installed by a licensed electrician.
- · Before commencing installation turn off and isolate the electrical supply
- \cdot Risk of accidental contact with live parts. Do not energise with product open or disassembled.
- · The only replaceable part is the battery
- \cdot Do not attempt to service other parts of the fitting as this will void the warranty
- \cdot After installation allow the battery to charge for 24 hours before carrying out discharge testing.
- \cdot Warning: all maintenance, such as battery change on this luminaire, to be performed by qualified personnel only. De-energise all supplies before maintenance.
- · As the installer, it is your responsibility to ensure you comply to all relevant building and safety codes. for example the BCA, AS3000
- \cdot The replacement of the battery is needed when they no longer meet their rated duration of operation after the corresponding recharge period.
- · For indoor use only
- \cdot Dongguan Evolt Electronics Co., Ltd. No.3 Qinghu East Road Yuliangwei Village, Qingxi TownDongguan City, Guangdong, China 523649



Wiring Diagram













Photometrics









